

FEATURES

- The preferred pump frame in the car wash self-service industry
- Dual crankshaft for convenience
- Forged brass manifold with an exclusive lifetime warranty
- Large-capacity, die-cast, anodized aluminum oil-bath crankcase
- Over-sized connecting rods for maximum life
- Heavy-duty tapered roller bearing.
- Solid ceramic plungers with continuously lubricated packings
- Unitized stainless steel inlet and discharge valves



SPECIFICATIONS

Pump Model	CW2040
Maximum Volume	5.0 GPM @ 1500 PSI, 1250 RPM
Max. Discharge Pressure	2500 PSI @ 3.0 GPM, 750 RPM
Maximum Pump Speed	1250 RPM @ 5.0 GPM, 2000 PSI
Maximum Inlet Pressure	125 PSI
Bore	.787 in. / 20 mm
Stroke	.630 in. / 16 mm
Crankcase Oil Capacity	33.8 oz.
Maximum Fluid Temp.	165°F
Inlet Port Thread	1/2-14 BSPP-F
Discharge Port Thread	3/8-19 BSPP-F
Shaft Diameter.	.945 in. / 24 mm Dual Shaft
Weight	30 lbs.
Dimensions	11.4 x 10.8 x 7.2 in.

DIMENSIONAL DRAWING



